



Wood-Lok™ 100

Virgin Wood Fiber



PRODUCT OVERVIEW:

Wood-Lok 100 is packaged in 50 lb bags and is a natural virgin wood fiber mulch for use in hydraulic planting. It is a high quality 100% wood fiber hydroseeding mulch manufactured under constant production control checks. It is manufactured in size and texture for optimum performance through a fiberization process that involves high temperature, steam, dying, drying and packaging.


Wood-Lok 100 Hydromulch is manufactured from virgin, fresh cut, selected, clean pine and poplar wood chips and meets or exceeds specifications and standards typical for Wood Fiber Hydromulch.

When applied, Wood-Lok 100 **long strand** fibers twist and lock with each other as they cure. This forms a protective mulch mat that aids in erosion control, holding the seeds in place, and providing an excellent environment for seed germination.

Wood-Lok 100 is designed to load quickly in hydroseeding equipment. The fibers are sized for maximum loading in the tank and will produce a homogeneous slurry with the water, seed and fertilizer.

Wood-Lok 100 will go into slurry suspension during the mixing process and will remain in suspension during the application process.

Wood-Lok 100 is green in color allowing for visible application assistance at maximum pumping distances. This allows the operator to apply an even application of material.



FEATURES & ADVANTAGES:

- Made from selected, fresh cut, clean, whole wood chips
- **Long strand** wood fibers stay in uniform suspension and blend easily with seed and fertilizer
- High loading and enters into the slurry quickly
- Forms a stable mulch mat that will hold the seed in place
- Provides a favorable microclimate for seed germination
- Helps establish grasses for erosion control, as well as fine turf
- Green dye assists in even application
- Wood-Lok 100 has no growth inhibiting factors
- Wood Fibers decompose after plants have established

APPLEGATE MULCH
1000 HIGHVIEW DRIVE
WEBBERVILLE MI 48892
HEADQUARTERS: 517-521-3545
FAX: 517-521-3597
800-627-7536 TOLL FREE
AskUs@ApplegateMulch.com

Worldwide Supplier

RECOMMENDED APPLICATION AND LOADING RATES:

RECOMMENDED MINIMUM APPLICATION RATE:

- 1,500 pounds per acre on flat to 5H:1V slopes

TANK LOADING RATE:

- 50 lbs per 100 gallon of water for tower gun application
- 45 lbs per 100 gallon of water for hose application

SPECIFICATIONS:

- Moisture content: 12.0%±3.0%
- Organic matter (oven dried basis): 99.3%±0.2%
- Ash content (oven dried basis): 0.7%±0.2%
- Average pH @ 3% concentration: 4.8 ±0.5
- Water holding capacity (per 100 grams oven dry fiber): min 1,250 gms.
- Color: Green
- Material Safety Data Class: Naturally occurring material
- Functional Longevity: 3 to 6 months

Manufacturer of the finest hydroseeding products.
Applegate's most appreciated benefit:

We listen, teach, serve, and stand behind you 100%.

Let us prove it. Call us with any concern.

1.800.627.7536

We've always been green.
Sustainable & earth-friendly since 1980



FACILITIES IN: ARIZONA ~ COLORADO ~ GEORGIA ~ KENTUCKY ~ LOUISIANA ~ MICHIGAN ~ PENNSYLVANIA ~ WISCONSIN
Then God said, "Let the land burst forth with every sort of grass"...and so it was...and God saw that it was good. - Genesis 1:11-12